# ARDRICH HAND DRYERS



### **ARDRICH A260**

HIGH EFFICIENCY - ANTIMICROBIAL

A260M (WHITE/SS) HD15300 A260SP (STAINLESS STEEL) HD15304

- FAST DRY TIME
- 1.2 MM 304 STAINLESS STEEL
- ANTIMICROBIAL INFUSED PLASTICS
- FULLY AUTOMATIC INFRA-RED OPERATION
- ENERGY EFFICIENT VERY LOW OPERATING COST
- SLIM UNOBTRUSIVE PROFILE
- LONG LIFE MOTOR AND CARBON BRUSHES

SAFE SURFACES. Our revolutionary antimicrobial infused components inhibit the growth of microbes including Staphylococcus and E.coli. Components are manufactured from special resins using EPA approved silver ion technology that infuses plastic parts and coatings with antimicrobial properties.

#### **SPECIFICATIONS**

Construction: Enclosure - 1.2 mm 304 Stainless Steel, Base - ABS FR, Fan Housings - FR, Outlet - Nylon FR. All plastics are flame retardant to UL94 VO, Class I double insulated, enclosure splash/drip proof to IPX4, non-corrosive. Gross weight 3.33 kgs. Shipping weight 3.61 kgs. Electrical rating 220-240 V~ 50-60Hz, 2.19 kW, 9.5AMP Noise level 69 dB. Air volume 5.4 M3/min. Air velocity 175 km/hr.

Generally, one hand dryer is recommended for every two hand basins. For heavy use in large washrooms, use two hand dryers for every three

#### **ELECTRICAL SAFETY APPROVALS**

AS3304, AS3300, NZ6362, NZ6300, IEC335-2-23:1996, IEC 335-1:1991 incl Amend 1, EN55014, EN50082-1, EN60555-2/3, International CB Text Certificate No. AU0182, Certificate of suitability No. Q070I41

### **ELECTRICAL CONNECTION & ADDITIONAL NOTES**

This dryer is a Class I product and is required to be earthed/grounded. Dryers are provided with a supply cord and plug. Dryer(s) may be fixed wired. Wiring should emerge from the wall at the position marked - Fixed wiring entry.

#### **TOTAL SATISFACTION WARRANTY**

Electronic Control Only Warranty - 5 year All other components - 5 years

DISABLED PERSON COMPLIANT (8)



EMC COMPLIANT 🕜 Z184





A260SP



A260M Gloss White Powder Coat over 304 Stainless Steel

# **ARDRICH HAND DRYERS**



### **ARDRICH A260**

**HIGH EFFICIENCY - ANTIMICROBIAL** 

A260M (WHITE) HD15300 A260SP (STAINLESS STEEL) HD15304





A260M

#### **RECOMMENDED MOUNTING HEIGHTS**

From the floor to the bottom of the dryer:

Men's washrooms - 1200mm

Women's washrooms - 1150mm

Children's washrooms - ages up to 10 860mm

Children's washrooms - ages up to 16 1120mm

Disabled person's washrooms - 1015mm

#### **DRYER DIMENSIONS**

 Height 273 mm

 Width 256 mm

 Depth 173 mm



